

# PRODUCT DATA SHEET

## AIRTRONIC S2 COMMERCIAL D2L 12V



Second-generation fuel-powered air heater with 2 kW heating power for heating driver's cabs in trucks, transporters, minibuses, motor homes and motor and sailing yachts.

### ADVANTAGES:

- Interfaces: CAN, LIN (only 12 V), S+
- Service life 5,000 h
- Brushless motor
- Use of the latest EasyStart Pro and EasyStart Web control units
- Diagnostics and parameter assignment via EasyScan
- Starting capability down to  $-46\text{ }^{\circ}\text{C}$
- Stepless heating performance control
- Noise emissions optimized
- Use of acoustically improved metering pump
- Integrated altitude sensor: Automatic altitude adjustment up to 3,000 m
- Optimized combustion

## AIRTRONIC S2 COMMERCIAL D2L 12V

Order number	252721050000
Voltage (v)	12
Medium	Air
Fuel	Diesel



## CONTROL STAGES

Control stages	Start	Small	Large
Electrical power consumption without water pump	100 W	6 W	31 W
Power		850 W	2,200 W
Fuel consumption		0.1 l/h	0.28 l/h

## ATTRIBUTES

Dimensions (l/w/h)	mm x mm x mm
Medium	Air
Operation suitable to x altitude	3,000.00
Upper voltage limit	16.00
Lower voltage limit	10.50